

GAGE254/0201-92-18

C-mount Bi-telecentric Lens

- Superior bi-telecentric design, distinguished imaging quality;
- Largest FOV from 26mm upto 300mm;
- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



| Optical Specifications | |
|------------------------------------|-------------|
| Magnification (x) | 0.201 |
| Object Field of View (Фтт) | 92 |
| Working Distance (mm) | 254±3 |
| Max Sensor Size (Фmm) | 18.5 (1.1") |
| Best Aperture (F/#) | 8 |
| Telecentricity typical (max) (deg) | <0.1 |
| Distortion typical (max) (%) | <0.1 |
| MTF30 (lp/mm) | >105 |
| Depth of Field (mm) | ±6.5 |
| Length of I/O (mm) | 498.3 |

| Field of View (mm × mm) | | |
|---------------------------|---------------------|--|
| 14.13x10.6w ith IMX304 | 70.30x52.74 | |
| Mechanical Specifications | | |
| Mount | С | |
| Length (mm) | 226.8 | |
| Compatible Lighting | | |
| Telecentric LED Lighting | VCL-100-xW-y | |
| | Beam Diameter 100mm | |

Notes:

- 1.Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
- 2.Length of I/O = WD + Length + Back Focal Length.



